



Declaration
of Performance



Multi-Fix 9 in 1

ADHESIVES & SEALANTS

HYBRID **FUSION+**




HIGH PERFORMANCE
SUPERIOR BOND STRENGTH
HYBRID POLYMER TECHNOLOGY



CONCRETE




BRICK



STONE



WOOD




MDF




METAL



GLASS



PLASTIC



CERAMIC

TIMco Multi-Fix 9in1 Universal Adhesive & Sealant



DECLARATION OF PERFORMANCE In accordance with Annex III of Regulation (EU) No 305/2011 (Construction Product Regulation)

DOP101v1

1: UNIQUE IDENTIFICATION CODE OF PRODUCT-TYPE

TIMCO MULTI-FIX 9IN1 UNIVERSAL ADHESIVE & SEALANT

2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
 - Batch number: See product packaging

3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
 - Sealants for façade elements
 - Sealants for sanitary joints
 - Sealants for pedestrian walkways

EN 15651-1: F-EXT-INT-CC (CLASS 25HM)
EN 15651-3: S (CLASS XS3)
EN 15651-4: PW-EXT-INT-CC (CLASS 25HM)

4. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):
 - T. I. Midwood & Co. Ltd, Green Lane, Wardle, Nantwich, Cheshire, CW5 6BJ

5. Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2):
 - Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
 - System 3
 - System 3 for reaction to fire

7. In case of declaration of performance concerning a construction product covered by a harmonized standard:
 - The notified body SKZ – TeConA GmbH (1213) performed the initial type testing according to EN 15651-1 / EN 15651-3 / EN 15651-4 and reaction to fire under system 3 and issued a: test report.

DECLARATION OF PERFORMANCE

TIMco Multi-Fix 9in1 Universal Adhesive & Sealant

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

- Not relevant

9. Declared performance

Conditioning: Procedure B (according to ISO 8340)

Substrate: Mortar M1 (with primer P03)

Glass (without primer)

Anodised aluminium (without primer)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-1:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10 %	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
Durability	Pass	

Substrate: Glass (without primer)

Anodised aluminium (without primer)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-3:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Vertical flow resistance	≤ 3 mm	
Loss of volume	≤ 20 %	
Tensile properties at maintained extension after water immersion	NF	
Extension after water immersion	3	
Microbiological growth	Pass	
Durability	Pass	

Substrate: Mortar M1 (with primer P03)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-3:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Tensile properties at maintained extension	NF	
Loss of volume	≤ 10 %	
Tear resistance	NF	
Adhesion / cohesion properties at maintained extension after 28 days water immersion	NF / change of secant modulus: ≤ 50 %	
Adhesion / cohesion properties at maintained extension after 28 days salt water immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
Durability	Pass	

(*) See material safety data sheet

NPD: No Performance Determined

NF: No Failure

NR: Not required

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not relevant.

TIMco Multi-Fix 9in1 Universal Adhesive & Sealant



10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

UNIQUE IDENTIFICATION CODE OF PRODUCT-TYPE
TIMCO MULTI-FIX 9IN1 UNIVERSAL ADHESIVE & SEALANT

A handwritten signature in black ink, appearing to be 'Simon Midwood', is written over the signature line.

Signed by:

Name: Simon Midwood

Position: Managing Director

Date & Location: 10. 08 . 2018
TIMco House, CW5 6BJ



This declaration is the responsibility of the importer

T.I Midwood & Co. Ltd. Green Lane, Wardle, Nantwich, Cheshire, CW5 6BJ