

TIMco Safety Frame Cramps



DECLARATION OF PERFORMANCE

DOP26 v2

We here by declare the following designated products

TIMco Safety Frame Cramps Sizes 100mm - 200mm

For the Harmonised Technical Specification: EN 845-1: 2013 Specification for ancillary components for masonry - Part 1: Ties, tension straps, hangers and brackets.

Intended Use : Asymmetrical Shear Tie with 3 holes in the upstand for connecting a new masonry leaf to an existing structure.

Notified Body: Lucideon Limited, Queens Road, Penkhull, Stoke on Trent ST4 7LQ. Tel. +44 (0)1782 764428

Notified Body Number: 1289

The system of assessment and verification of constancy of performance for this construction product conforms to: System 3

Essential Characteristics

Compression Load Capacity: 1290N

Tensile Load Capacity—top hole 480N

Displacement at 1/3 Load — Compression 0.56mm

Displacement at 1/3 Load—Tensile 1.01mm

Water Shedding Capability: Resistant

Durability: Material Reference 3: Austenitic Stainless

Steel Strip Grade 304 18/8 comp. to BS EN 10088/1

Embedment Depth: 62.5mm

Minimum Mortar Designation: (iv)

Minimum Mortar Joint Width: 10

Recommended Spacing: As required

This declaration of conformity is valid until there is a significant change in the product and declared characteristics. ie. raw material or change in production process.

Signed by:

Name: *Simon Midwood*

Position: *Managing Director*

Date & Location: *30. 11. 2015
TIMco House, CW5 6BJ*

This declaration is the responsibility of the importer

T.I Midwood & Co. Ltd. Green Lane, Wardle, Nantwich, Cheshire, CW5 6BJ

